



## FILTER HOUSINGS

### DP BIG

**Mono, Duo and Trio patented and registered manifold filter housings designed to fit BIG filter cartridges with outer diameter 4.5".** IN/OUT connections 1", 1 1/2" with plastic BSP or NPT threads. Atlas Filtri BIG filter cartridges are available in a range of polypropylene wound thread models (single and multi-layer) and carbon block models (CTO, VOC, Pb, Cyst), and in a new range of pleated filter cartridges (CS BIG, TS BIG, SA BIG) and cylindrical filter cartridge (RA BIG). Cartridge heights 10", 20". Models with transparent (TS) or opaque (AB) bowls.

**M** models with 2 manometers (only BSP versions).

**S** models with discharge valve for self-cleaning performance (only BSP versions), provided with a drain funnel to protect potable water from back-flow pollution, in compliance with UNI EN 1717 - 11/2002.

**PS PM** models with drain and manometer plugs.

**Max working pressure:** 8,3 bar (120 psi)

**Max working temperature:** 45°C (113°F).

**Accessories included:** spanner, Lubrikit.

**Accessories on demand:** metal wall bracket, KIT AUTO (discharge automation kit), KIT FRAME, KIT LEG (for DP BIG Frame).

**Main materials:** Reinforced PP, PET.

## LUBRIKIT

Single-dose lubricant for housing o-ring.



10" MONO TS



10" S M MONO TS



20" MONO AB

**DRAIN FUNNEL**  
Back-flow  
preventing device  
UNI EN 1717-11/2002